

General	
Degree of Mobility	Portable Equipment
Expected Lifetime	5 Years from date of manufacture
Standards	
Safety:	Class I (IEC 60601-1); Type BF (IEC 60601-1); IPXO - Ordinary Equipment (IEC 60601-1)
Operating environment	
Temperature:	+15°C to +35°C (59°F to +95°F)
Relative humidity:	15% to 90% at 40°C non-condensing
Storage and handling	
Temperature:	0°C to +50°C (32°F to +122°F)
Relative humidity:	< 95%, non-condensing
Electrical specifications	
Rated Input Current:	0.5 A
Rated Input Voltage:	Nominal: +5 V DC; Acceptable range: 4.30 V to 5.50 V
PC power supply	
The PC that Capella <sup>2</sup> is connected to should have a grounded power supply	
Technical specifications - ER-10D Probe	
Connector	8-Pin mini DIN
Cable Length	6 feet ( 1.83 meters)
Net Weight	3.6 oz. (100 grams) approx.
Maximum Output	109 dB SPL - 64 dB SPL (frequency dependent) measured in Zwislocki coupler
Technical specifications - OAE System	
The OAE amplifier, inside Capella <sup>2</sup> , contains the low-pass filters, high-pass filters and gain settings used to acquire otoacoustic emission recordings from an ER-10D OAE probe, for OTOsuite.	
Accessories	
ER-10D OAE Probe, USB cable , Wall Mount Kit (optional). <b>Disposable accessories:</b> MADSEN Capella <sup>2</sup> Starter Kit, ER-10D OAE Probe Tips, Probe cleaning tool, Plastic eartips, Foam eartips.	
System requirements	
For system requirements, please refer to the OTOsuite data sheet.	

*Specifications are subject to change without notice. Copyright © Natus Medical Denmark ApS. Doc. No. 7-26-2669-EN/01 - Part No. 7-26-26609-EN (213960)*