

Video system	
Sensor resolution	720 (H) x 720 (V) pixels
Optical data	
Minimum working distance	10 mm (0.4 inches)
Preheater	
Preheater power	Heats camera distal tip to approx +5°C (9°F) above ambient temperature after 5 minutes of activation
Electrical data	
USB plug	USB, type A (LED power supply/Camera/Pre-heating)
Mechanical data	
Cable length	2700 mm (8.86 feet)
Weight including cable	250 g (8.8 ounces)
Storage environment	
Temperature	-20°C to +60°C (-4°F to +140°F)
Relative humidity	<90%, non-condensing
Air pressure	500 hPa to 1060 hPa
Operating environment	
Temperature	+10°C to +30°C (+50°F to +86°F)
Air humidity	30% to 75%, non-condensing
Air pressure	600 hPa to 1060 hPa
Essential performance	
Aurical Otocam 300 has no essential performance.	
Standards	
Patient Safety	IEC 60601-1:2005+AMD1:2012 and EN 60601-1:2006+A1:2013 CAN/CSA-C22.2 NO. 60601-1:14 Class II; applied part Type BF; IPX0
	Endoscopic equipment: IEC 60601-2-18:2009 and EN 60601-2-18:1996 + A1:2000
EMC	IEC 60601-1-2:2007 and EN 60601-1-2:2007 IEC 60601-1-2:2014 and EN 60601-1-2:2015
System requirements	
For system requirements, please refer to the Otosuite data sheet.	

Specifications are subject to change without notice. Copyright © Natus Medical Denmark ApS. Doc. No. 7-26-9010-EN/10 - Part No. 7-26-90100-EN (216990)